

IVR-SAN 25

(25% Active Sodium Chlorite)

ACTIVE INGREDIENT: Sodium Chlorite*25%
OTHER INGREDIENTS:.....75%
*AVAILABLE CHLORINE.....39%

CONTAINS 2.58 LBS. OF SODIUM CHLORITE PER GALLON AT 70°F

**KEEP OUT OF REACH OF CHILDREN
DANGER**

FIRST AID	
If in eyes:	*Hold eye open and rinse slowly and gently with water for 15 -20 minutes. *Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. *Call a poison control center or doctor immediately for treatment advice.
If on skin or clothing:	*Take off contaminated clothing *Rinse skin immediately with plenty of water for 15-20 minutes. *Call a poison control center or doctor for treatment advice if burning or irritation of the skin persists.
If swallowed:	*Have person drink a glass of water immediately if able to swallow. *Call a poison control center or doctor immediately for treatment advice. *Do not induce vomiting unless told to do so by the poison control center or doctor. *Do not give anything by mouth to an unconscious person.
If Inhaled:	*Move person to fresh air and monitor for respiratory distress. *If cough or difficulty in breathing develops, consult a physician immediately. *If person is not breathing, call 911 or an ambulance, then give artificial respiration. *Call a poison control center or doctor for further treatment advice.
For emergency information call: 1-800-424-9300 (24 hours) Have the product container or label with you when calling a poison control center or doctor or going to treatment.	
NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.	

Sold by:



8820 Old Hwy. 99 SE, Tumwater, WA 98501/ 360-943-6063

EPA Reg. No. 5382-43-43553

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS & DOMESTIC ANIMALS

DANGER. Corrosive. Causes irreversible eye damage and skin burns. Harmful if swallowed. Irritating to nose and throat. Do not get in eyes, on skin, or on clothing. Wear protective eyewear such as splash-proof goggles, face-shield, or safety glasses. Wear protective clothing and rubber gloves when handling this product. Avoid breathing mists or fumes. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove and wash contaminated clothing before reuse.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to the discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS

Dry sodium chlorite is a strong oxidizing agent. This product becomes a fire or explosive hazard if allowed to dry. Mix only into water. Contamination may start a chemical reaction with generation of heat, liberation of hazardous gases (chlorine dioxide a poisonous, explosive gas), and possible fire and explosion. Do not contaminate with garbage, dirt, organic matter, household products, chemicals, soap products, paint products, solvents, acids, vinegar, beverages, oils, pine oil, dirty rags, or any other foreign matter.

DIRECTIONS FOR USE

It is a violation of Federal law to use the product in a manner inconsistent with its labeling.

Directions for Controlling the Growth of Algae in Recirculating Cooling Water Towers

1. Clean badly fouled systems before starting treatment. 2. When algae are visible, add an initial dosage of 8.4 fluid ounces of **IVR-SAN 25** per 1,000 gals. of water in the system. Repeat if necessary until control is evident. 3. Where algae control is evident, use a subsequent dose of 4.2 fluid ounces of **IVR-SAN 25** solution per 1,000 gals. of water in the system twice a week or as needed to maintain control. 4. Add **IVR-SAN 25** directly to the cooling tower drip pan (cold water basin) near the inlet to the recirculating pump.

Directions for Use in the Mechanical or Electrolytic Generation of Chlorine Dioxide as a Disinfectant, or for Microorganism or Mollusk Control and as a Chemical Oxidant in Aquatic Systems.

Feed requirements: Feed rates of **IVR-SAN 25** will depend on the severity of contamination and the degree of control desired. The exact dosage will depend on the size of the system and residual necessary for effective control. Depending on the generator type, **IVR-SAN 25** may be diluted at the point of use to prepare a 3% to 25% active aqueous solution for use in chlorine dioxide generators.

Some examples of industrial applications of chlorine dioxide include:

- Potable water disinfection and removal of sulfide.
- Control of bacterial slime and algae and mollusks in industrial recirculating and one-pass cooling systems.
- Biocontrol in food processing flumes, water-using equipment, cooling water, and recycled waters.
- Disinfection of sewage and plant wastes.
- Destruction of phenolics, simple cyanides and sulfides by chemical oxidation.
- Bacterial slime control in white water paper mill systems.
- Bacterial control in oil well and petroleum systems.

See product bulletins (or Technical Data Sheets) for specific application instructions. Your CH₂O representative can guide you in application techniques.

Method of feed: Large amounts of chlorine dioxide can be generated by several common methods, including:

1. The chlorine method which utilizes an **IVR-SAN 25** solution and chlorine gas, or
2. The hypochlorite method which utilizes an **IVR-SAN 25** solution, a hypochlorite solution, and an acid, or
3. The Acid-chlorite method which utilizes an **IVR-SAN 25** solution and an acid, or
4. The electrolytic method which utilizes a **IVR-SAN 25** solution, with sodium chloride added as needed.

Your CH₂O representative can guide you in the selection, installation and operation for feed systems. Consult product bulletin and also the instructions on the chlorine dioxide generation system before using **IVR-SAN 25**.

User is responsible for compliance with applicable federal, state and local laws regarding proper use and disposal of the chlorine dioxide generated.

Directions for Use in Controlling Microbial Population in Poultry Processing Water

Chlorine dioxide generated from **IVR-SAN 25** may be used as an antimicrobial agent in water used in poultry processing, provided that the residual concentration of chlorine dioxide does not exceed 3 ppm, as determined by an appropriate method in accordance with 21 CFR 173.300.

For treatment of poultry chill water, apply **IVR-SAN 25** as necessary through a chlorine dioxide generation system to maintain a residual concentration of up to 3 parts per million (ppm) chlorine dioxide in the chiller water.

Food Plant Process Water Treatment

Chlorine dioxide generated from sodium chlorite is effective for use in controlling microbiological growth in flume water and other food processing water systems such as chill water systems and hydrocoolers. The required dosages will vary with process conditions and the degree of contamination present. Depending on the requirements of the specific water system, sodium chlorite should be applied continuously or intermittently through a chlorine dioxide generating system to achieve a chlorine dioxide residual concentration between 0.25 and 5.0 ppm. Water, containing up to 3 ppm residual chlorine dioxide may be used for washing fruits and vegetables that are not raw agricultural commodities in accordance with 21 CFR 173.300. Treatment of the fruits and vegetables with chlorine dioxide must be followed by a potable water rinse, or by blanching, cooking or canning.

Aqueous Disinfection Systems for CIP Cleaning

If the concentration of chlorine dioxide generated from **IVR-SAN 25** exceeds 5.0 ppm, a potable water rinse should follow treatment. Care should be taken to ensure the biological and chemical quality of the potable water.

Industrial Cooling Water Treatment

For control of bacterial slime and algae in industrial recirculating and one-pass cooling systems, the required dosages will vary depending on the exact application and the degree of contamination present. The required chlorine dioxide residual concentrations range between 0.1 and 5.0 ppm. Chlorine dioxide may be applied either continuously or intermittently. The typical chlorine dioxide residual concentration range is 0.1 - 1.0 ppm for continuous doses, and 0.1 - 5.0 ppm for intermittent doses. The minimum acceptable residual concentration of chlorine dioxide is 0.1 ppm for a minimum one minute contact time.

Potable Water Treatment

Chlorine dioxide (ClO₂) is used as both an oxidant and a disinfectant in drinking water treatment.

The required dosages will vary with source water conditions and the degree of contamination present. For most municipal and public potable water systems, a chlorine dioxide residual concentration of up to 2 ppm is sufficient to provide adequate disinfection. Residual disinfectant byproducts must be monitored as required by the National Primary Drinking Water Regulations (40 CFR part 141) and state drinking water standards.

Bacterial Slime Control in Paper Mills

Chlorine dioxide generated from sodium chlorite is effective for use in controlling microbiological growth in white water paper mill systems. The required dosages will vary with the degree of microbiological and process contamination present. Depending on the specific requirements of the system, sodium chlorite should be applied continuously or intermittently through a chlorine dioxide generating system to achieve a chlorine dioxide residual of between 0.1 and 0.5 ppm. Intermittent treatments should be repeated as often as necessary to maintain control.

Mollusk Control in Water Systems

Chlorine dioxide generated from sodium chlorite may be used for mollusk control in commercial and industrial recirculating and one-pass cooling water systems. The required dosages will vary with the system type, system conditions, the degree of water contamination present and the desired level of control. Depending on the extent of the infestation, sodium chlorite may be applied either continuously or intermittently through a chlorine dioxide generating system to achieve the necessary chlorine dioxide residual concentration.

Veliger Control: Maintain a continuous chlorine dioxide residual of 0.1-0.5 ppm.

Intermittent Dose: Apply chlorine dioxide to obtain a chlorine dioxide residual concentration of 0.2 - 25 ppm. Repeat as necessary to maintain control.

Continuous Dose: Maintain a chlorine dioxide residual concentration of up to 2 ppm.

Wastewater Treatment

Chlorine dioxide (ClO₂) is effective as both a disinfectant and an oxidant in wastewater treatment.

The required dosages will vary with water conditions and the degree of contamination present. For most municipal and other wastewater systems, a chlorine dioxide residual concentration of up to 5 ppm is sufficient to provide adequate disinfection. For sulfide odor control, between pH 5-9, a minimum of 5.2 ppm (wt) of chlorine dioxide should be applied to oxidize 1 ppm of sulfide (measured as sulfide ion). For phenol destruction, at pH less than 8, 1.5 ppm chlorine dioxide will oxidize 1 ppm phenol; at pH greater than 10, 3.3 ppm chlorine dioxide will oxidize 1 ppm phenol.

Irrigation and Irrigation Water Systems

Irrigation: To control bacteria, algae, and slime in irrigation piping and emitters for fields and greenhouse/hothouse applications treat continuously or intermittently.

Irrigation Water Systems: To control bacteria, algae, slime, and reduce nitrification treat continuously or intermittently.

Intermittent Dose: Add 42 to 210 pounds of chlorine dioxide per million gallons of water (5 to 25 ppm).

Continuous Dose: Add 2 to 16 pounds of chlorine dioxide per million gallons of water (0.25 to 2 ppm).

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food or feed by storage or disposal. Keep product in tightly closed container when not in use. Don't drop, roll or skid drum. Keep upright. Always replace cover. Store in a cool, dry well-ventilated area away from heat or open flame.

EMERGENCY HANDLING: In case of contamination or decomposition, do not reseal container. If possible, isolate container in open and well-ventilated area. Flood with large volumes of water. If fire occurs, extinguish fire by applying large quantities of water. Any unopened drums near the fire should be cooled by spraying with water.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Nonrefillable Container.

Do not reuse or refill this container. Offer for recycling if available. Offer for reconditioning if appropriate. Triple Rinse or Pressure Rinse container promptly after emptying.

Triple Rinse as follows: Empty remaining contents into application equipment or a mix tank. Fill the container 1/4 full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times.

Pressure Rinse as follows: Empty the remaining contents into application equipment or a mix tank and continue to drain for 10 seconds after the flow begins to drip. Hold container upside down over application equipment or mix tank or collect rinsate for later use or disposal. Insert pressure rinsing nozzle in the side of the container, and rinse about 40 PSI for at least 30 seconds. Drain for 10 seconds, after the flow begins to drip.