



8820 Old Hwy 99 SE, Olympia, Washington 98501, USA
360-943-6063 800-562-6184 FAX 360-352-4813 www.ch2o.com



ALUBRITE HEAVY-DUTY INHIBITED CAUSTIC CLEANER FOAMY CLEANER THAT CUTS THE HEAVIEST GREASE AND OIL BUILDUP FROM ALL TYPES OF METAL & OTHER FOOD CONTACT SURFACES

TYPICAL APPLICATIONS

ALUBRITE is designed to prevent mineral buildups in an alkaline system where chlorine sources may be present.

CONCENTRATED

ALUBRITE's heavy-duty formulation allows low use-solution concentrations, resulting in low cost cleaning with optimum performance. Suggested use-rate is 40 parts water to 1 part **ALUBRITE**.

CONVENIENT

ALUBRITE is a liquid cleaner which can be accurately and efficiently dispensed through automatic feed and control systems.

MODERATE FOAMING

ALUBRITE provides a moderate amount of foam to aid in soil penetration during cleaning. Upper portions of conveyors and vessels may be cleaned by foam contact.

FREE RINSING

Chelants and wetting agents in **ALUBRITE** are carefully selected to provide excellent rinsing ability and inhibit the formation of calcium carbonate (CaCO₃) precipitate in the rinse cycle.

SAFER THAN POWDERS

ALUBRITE produces less heat when added to water than dry products. Powder dilution heat can cause an injurious "flash back."

GENERAL DIRECTIONS

Food Plant Cleaning Concentrations

High Pressure Cleaning 0.25 to 1 oz/gal

Soak Tank 0.50 to 3 oz/gal

Hand Brush 0.50 to 3 oz/gal

Foam Cleaning*0.75 to 1 oz/gal

*Used with **FOAM MAX 839** at 0.3 oz/gal

High pressure cleaning requires 1 ounce **ALUBRITE** to 1 gallon of warm water for cleaning fillet machines, skinners, conveyors, trim tables, glazers, and associated hoppers and equipment.

PHYSICAL PROPERTIES

Appearance Straw-Colored Liquid

Odor..... Slight

Foam..... Moderate

Rinsing Ability Excellent

pH of Use Solution..... 11.5-12.5

Specific Gravity 1.17-1.19

PRODUCT pH INDICATOR
----- acid ---- neutral ---- alkaline -----
0 1 2 3 4 5 6 7 8 9 10 11 12 13 14



Seller Warranty

Applies to all products sold by CH₂O, Inc., and is hereby communicated to all of its customers as a condition of sale.

Seller warrants that this product conforms to its chemical description and is reasonably fit for the purpose referred to in the directions for use when used in accordance with the directions under normal conditions. Buyer assumes the risk of any use contrary to such directions. Seller makes no other warranty or representation of any kind, express or implied, concerning the product, including **NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE**. No such warranties shall be implied by law and no agent of seller is authorized to alter this warranty in any way except in writing with a specific reference to this warranty. The exclusive remedy against seller shall be a claim for damages not to exceed the purchase price of the product, without regard to whether such a claim is based upon breach of warranty or tort. Jurisdiction for any issues arising from or relating to this product shall be in the courts of the State of Washington and the venue shall be Thurston County. Any controversy or claim arising out of or relating to this contract, or breach thereof, shall be settled by arbitration in accordance with the rules and procedures as stated in RCW 7.06 and shall be binding upon both parties without right to appeal, and judgment upon the award rendered by the Arbitrator(s) may be entered in any court having jurisdiction thereof.

January 18, 2002 (Rev. 09-11)

