



Product Bulletin

8820 Old Highway 99 SE, Olympia, Washington 98501, USA
360-943-6063 800-562-6184 FAX 360-352-4813 www.ch2o.com

EVER-KLEEN 9241
LOW-FOAMING DETERGENT/DEGREASER
CUTS GREASE & OILS EFFECTIVELY

TYPICAL APPLICATIONS

EVER-KLEEN 9241 is recommended for use on floors, walls, vehicles, parts washing, floor scrubbers, and general equipment cleaning.

CONVENIENT & SAFER THAN POWDERS

EVER-KLEEN 9241 is a liquid cleaner that can be accurately and efficiently dispensed through automatic feed and control systems. Unlike some dry alkaline cleaners, it produces no heat upon dilution with water.

LOW-FOAMER

EVER-KLEEN 9241 is a low-foaming product that does not generate large amounts of suds during application.

FREE RINSING

Chelants and wetting agents in EVER-KLEEN 9241 are carefully selected to provide excellent rinsing ability and inhibit the formation of hard water deposits.

SAFETY

EVER-KLEEN 9241 is strongly alkaline. Wear gloves and eye protection when handling this product. Never mix this product with other materials.

GENERAL DIRECTIONS

Bulk Tank Cleaning

1) Add 1 gallon EVER-KLEEN 9241 per 50 gallons of hot water in plastic or stainless steel container and spray on equipment.

2) Let detergent set for a minimum of 20 minutes; rinse completely before surface dries. If heavy starch or protein buildups are present, add 1/2 pint of sodium hypochlorite (12.5 percent) to above use-solution and apply to noncorrosive surfaces.

3) If a heavy mineral or detergent scale is present, use a heavy acid wash or foam application. Otherwise, use an acid rinse to neutralize residual alkalinity.

GENERAL DIRECTIONS (Cont'd)

Exterior Stainless Steel Surfaces

1) Mix 2 ounces EVER-KLEEN 9241 per gallon of hot water and manually scrub or brush exterior surfaces. If foaming on vertical or overhead surfaces occurs, additional foaming agents might be needed.

2) Rinse all surfaces with water thoroughly after using and apply an acid rinse to neutralize residual alkalinity.

Concrete Floors

Using a portable sprayer, apply undiluted product onto grease or oil stains. Light brushing may be needed for heavy grease deposits. Let detergent sit for 20 minutes and rinse with water.

Floor Scrubbers

Use 1 to 2 ounces per gallon of water in the scrubber soap tank.

Parts Washing

Generally a dilution from 1:10 to 1:5 will be adequate to clean greasy parts. Rinse thoroughly with water. Do not use this product on aluminum, copper, brass, or galvanized surfaces.

General Surface Cleaning

Use 4 to 8 ounces per gallon of water. Rinse well after cleaning. Use with caution on painted surfaces and test a small area first before general application.

PHYSICAL PROPERTIES

Table with 2 columns: Property and Value. Properties include Appearance (Greenish Liquid), Odor (Mild), Foam (Moderate), Rinsing Ability (Excellent), pH of 1% Solution (11.5-12.5), and Pounds per Gallon (9.0-9.5).

PRODUCT pH INDICATOR
--- acid --- neutral --- alkaline ---
0 1 2 3 4 5 6 7 8 9 10 11 12 13 14

Seller Warranty

Applies to all products sold by CH2O, Inc., and is hereby communicated to all of its customers as a condition of sale.

Seller warrants that this product conforms to its chemical description and is reasonably fit for the purpose referred to in the directions for use when used in accordance with the directions under normal conditions. Buyer assumes the risk of any use contrary to such directions. Seller makes no other warranty or representation of any kind, express or implied, concerning the product, including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE.

September 18, 2001 (Rev 08-06)

