



8820 Old Hwy 99 SE, Olympia, Washington 98501, USA
360-943-6063 800-562-6184 FAX 360-352-4813 www.ch2o.com

**Product
Bulletin**

FOAM-MAX 839

HIGHLY CONCENTRATED FOAM ADDITIVE FOR USE IN ALKALINE OR ACIDIC SOLUTIONS

CONCENTRATED

FOAM-MAX 839 is an extremely concentrated product, resulting in low-cost use-solutions while maintaining optimum performance.

CONVENIENT

Because **FOAM-MAX 839** is a liquid, it can be dispensed accurately and efficiently through automatic feed/control systems.

HIGH FOAMING

FOAM-MAX 839 provides an abundant amount of foaming to aid in soil penetration during cleaning processes. It is useful when the cleaning solution needs to contact upper portions of conveyors and vessels.

FREE RINSING

The wetting agents in **FOAM-MAX 839** provide excellent rinsing ability and inhibit the formation of calcium carbonate (CaCO₃) precipitate in the rinse cycle.

SAFETY & HANDLING PROCEDURE

While **FOAM-MAX 839** is a relatively inert material, it is suggested that safety glasses and impervious gloves be worn when handling the concentrated product. Read the Material Safety Data Sheet for further safety and handling details.

TYPICAL APPLICATIONS

FOAM-MAX 839 is recommended for use on conveyors, framework, augers, mixers, tile walls, floors, and general food processing equipment. Do not mix **FOAM-MAX 839** with chlorinated detergent or sanitizers.

GENERAL DIRECTIONS

For generating foam: Use 8 to 16 ounces (pint) of **FOAM-MAX 839** in 50 gallons of water that has already been made into a use-solution with an alkaline or acid-based cleaner. Mix well before use.

For manual cleaning of small parts and utensils: Use 1/3 to 1 ounce of **FOAM-MAX 839** per gallon of 130°F water. Clean parts with this solution, and then rinse thoroughly with fresh water.

For cleaning painted surfaces: Use 1/3 to 1 ounce of **FOAM-MAX 839** per gallon of 120°F to 160°F water. Brush, mop, or spray solution onto surface to be cleaned. Wash walls from bottom to top to avoid streaks on paint. Rinse with fresh water.

PHYSICAL PROPERTIES

Appearance Light Yellow Liquid
Odor Mild
Foam High
Pounds per Gallon..... 8.4-8.9
pH of 1% solution 7.0-9.0

Seller Warranty

Applies to all products sold by CH₂O, Inc., and is hereby communicated to all of its customers as a condition of sale.

Seller warrants that this product conforms to its chemical description and is reasonably fit for the purpose referred to in the directions for use when used in accordance with the directions under normal conditions. Buyer assumes the risk of any use contrary to such directions. Seller makes no other warranty or representation of any kind, express or implied, concerning the product, including **NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE**. No such warranties shall be implied by law and no agent of seller is authorized to alter this warranty in any way except in writing with a specific reference to this warranty. The exclusive remedy against seller shall be a claim for damages not to exceed the purchase price of the product, without regard to whether such a claim is based upon breach of warranty or tort. Jurisdiction for any issues arising from or relating to this product shall be in the courts of the State of Washington and the venue shall be Thurston County. Any controversy or claim arising out of or relating to this contract, or breach thereof, shall be settled by arbitration in accordance with the rules and procedures as stated in RCW 7.06 and shall be binding upon both parties without right to appeal, and judgment upon the award rendered by the Arbitrator(s) may be entered in any court having jurisdiction thereof.

September 30, 2002 (Rev 09-11)

