



8820 Old Hwy 99 SE, Olympia, Washington 98501, USA
 360-943-6063 800-562-6184 FAX 360-352-4813 www.ch2o.com



MXT-2 BIO-GUARD TREATMENT FOR COOLING TOWERS & AIR WASHERS

APPLICATION

Cooling towers provide a near-ideal environment for microbial proliferation. Warm water temperatures, nutrients, and constant exposure to the surrounding air encourage growth and virtually assure ongoing contamination by microorganisms. The U.S. Public Health Service Center for Disease Control & Prevention (CDC) has identified some of these organisms to cause human illness or death. OSHA Technical Manual Section II - Chapter 7 states that biocide control of such organisms is needed.

Unchecked microbial growth may also cause a rapid loss of heat-transfer efficiency by fouling piping, nozzles, packing, process heat exchangers, and drift eliminators. Growth under deposits or slime masses can yield accelerated localized corrosion of system metal components. These problems, due to growth and development of algae, bacteria, and fungi greatly reduce efficiency in a system and significantly increase operating costs.

Microbial organisms in nature vary considerably as a hazard to human health and in susceptibility to any particular bactericide. CH₂O's **BIO-GUARD** series offers a wide variety of biocide products, which have been shown effective against microorganisms found in cooling tower waters.

MXT-2 is a polymeric quaternary amine:

Poly (oxyethylene(dimethyliminio)ethylene (diemethyliminio)ethylene dichloride

MXT-2 aids in controlling microbial growth in water-cooling towers & air-washers. It is effective over a wide pH and temperature range and is non-foaming. **MXT-2** is noncorrosive and does not contain heavy metals.

SAFETY & HANDLING PROCEDURE

Use chemical resistant gloves and safety glasses or face shield when handling. Observe all safety precautions shown on the label and stated in the Material Safety Data Sheet.

EFFECTIVE CONDITIONS

MXT-2 is effective at most pH ranges found in normally operated cooling towers and industrial air washers. At a pH of 7.0 it is 3 to 30 times more effective than older technology quaternary amines. When used with oxidizing biocides, a synergistic effect has been observed.

DOSAGE & CONTROL

An initial slug addition of 2.9 to 7.3 fluid ounces of **MXT-2** per 1,000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 0.73 to 7.3 fluid ounces of **MXT-2** per 1,000 gallons of water should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon this relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made to the water sump of cooling towers. It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Consult product label for use directions relating to industrial air washing systems. Daily testing is recommended to maintain proper control. Failure to monitor and maintain treatment levels can cause damage. It is the customer's responsibility to monitor and maintain treatment levels.

PHYSICAL PROPERTIES:

pH of 1% Solution.....	5.0-7.0
Pounds per Gallon.....	8.4-8.9
Physical Appearance.....	Light Amber
Odor.....	Mild
Flash Point.....	N/A

Seller Warranty

Applies to all products sold by CH₂O, Inc., and is hereby communicated to all of its customers as a condition of sale.

Seller warrants that this product conforms to its chemical description and is reasonably fit for the purpose referred to in the directions for use when used in accordance with the directions under normal conditions. Buyer assumes the risk of any use contrary to such directions. Seller makes no other warranty or representation of any kind, express or implied, concerning the product, including **NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE**. No such warranties shall be implied by law and no agent of seller is authorized to alter this warranty in any way except in writing with a specific reference to this warranty. The exclusive remedy against seller shall be a claim for damages not to exceed the purchase price of the product, without regard to whether such a claim is based upon breach of warranty or tort. Jurisdiction for any issues arising from or relating to this product shall be in the courts of the State of Washington and the venue shall be Thurston County. Any controversy or claim arising out of or relating to this contract, or breach thereof, shall be settled by arbitration in accordance with the rules and procedures as stated in RCW 7.06 and shall be binding upon both parties without right to appeal, and judgment upon the award rendered by the Arbitrator(s) may be entered in any court having jurisdiction thereof.

April 9, 1998 (Rev 09-11)

