



8820 Old Hwy 99 SE, Olympia, Washington 98501, USA
360-943-6063 800-562-6184 FAX 360-352-4813 www.ch2o.com

**Product
Bulletin**

**WAX-AWAY
HEAVY-DUTY WAX & GREASE REMOVER
A CONCENTRATED CLEANER DESIGNED TO REMOVE WAX BUILDUPS ON
CONVEYORS, DRYERS, ROLLERS, BRUSHES & OTHER PROCESSING EQUIPMENT**

TYPICAL APPLICATIONS

WAX-AWAY is recommended for use on conveyors, framework, augers, mixers, tile walls, floors, and general food processing equipment.

WAX-AWAY is designed for the removal of grease, wax, and oily films on food processing equipment and structures. **WAX-AWAY** can be used on soft metals and is effective on tile, rubber, and plastic surfaces.

CONCENTRATED

WAX-AWAY's heavy-duty formulation allows low use-solution concentrations, resulting in low cost cleaning with optimum performance.

CONVENIENT

Because **WAX-AWAY** is a liquid cleaner, it can be dispensed accurately and efficiently through automatic feed/control systems.

MODERATE FOAMER

WAX-AWAY provides a moderate amount of foaming to aid in soil penetration during cleaning processes, where foam may contact upper portions of conveyors and vessels.

FREE RINSING

Selected chelants and wetting agents in **WAX-AWAY** provide excellent rinsing ability and inhibit the formation of calcium carbonate (CaCO₃) precipitate in the rinse cycle.

SAFETY & HANDLING PROCEDURE

This is an alkaline product. Eye contact will cause severe irritation and/or minor burns. Prolonged or repeated skin contact can cause irritation and possible dermatitis. Excessive inhalation of product mists can cause irritation to the respiratory system. Wear impervious gloves and safety glasses or goggles when handling product

GENERAL DIRECTIONS

WAX-AWAY can be applied by manual methods as in general housekeeping operations. Dilute 1 part **WAX-AWAY** with 10 to 20 parts water at up 120°F. In high pressure spray cleaning or CIP systems, a dilution of 1 part **WAX-AWAY** per 50 to 100 parts water at 140°-160°F is recommended. When used in steam cleaning equipment, use 1:10 to 1:20. In power floor scrubbers, use ranges from 1:10 to 1:80 depending on the soil load to be removed.

PHYSICAL PROPERTIES

Appearance	Clear Blue Liquid
Odor.....	Slight
Foam.....	Moderate
Rinsing Ability	Excellent
pH of Use Solution.....	11.5-12.5
Pounds per Gallon	8.8-9.3



Seller Warranty

Applies to all products sold by CH₂O, Inc., and is hereby communicated to all of its customers as a condition of sale.

Seller warrants that this product conforms to its chemical description and is reasonably fit for the purpose referred to in the directions for use when used in accordance with the directions under normal conditions. Buyer assumes the risk of any use contrary to such directions. Seller makes no other warranty or representation of any kind, express or implied, concerning the product, including **NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE.** No such warranties shall be implied by law and no agent of seller is authorized to alter this warranty in any way except in writing with a specific reference to this warranty. The exclusive remedy against seller shall be a claim for damages not to exceed the purchase price of the product, without regard to whether such a claim is based upon breach of warranty or tort. Jurisdiction for any issues arising from or relating to this product shall be in the courts of the State of Washington and the venue shall be Thurston County. Any controversy or claim arising out of or relating to this contract, or breach thereof, shall be settled by arbitration in accordance with the rules and procedures as stated in RCW 7.06 and shall be binding upon both parties without right to appeal, and judgment upon the award rendered by the Arbitrator(s) may be entered in any court having jurisdiction thereof.

March 6, 1998 (Rev 04-11)

