



8820 Old Hwy 99 SE, Tumwater, Washington 98501, USA
360-943-6063 800-562-6184 FAX 360-352-4813 www.ch2o.com



A-302 ALUMINUM BRIGHTENER

The appearance of weathered aluminum cleaned with this formula is quite different from the appearance of aluminum cleaned with traditional formulations. In addition to better cleaning, the formulation gives a brighter appearance without severe localized pitting.

A-302 should not be applied to glass. However, if the formulation does contact glass, prompt water rinsing will prevent etching.

Use 5 gallons of **A-302** per 50 gallons of water during the summertime and 7 to 8 gallons per 50 gallons of water in the winter. This diluted solution is sprayed on the dirty aluminum by drenching from bottom to top, then down again to the bottom. In 3 to 5 minutes, before the foam begins to gall and streak, a similar bottom-to-top-to-bottom rinse with clean water is applied, leaving a clean and bright aluminum surface.

NOTE: For stainless steel, use the same formula used for aluminum. The inhibitive properties of this formulation prevent attack of the stainless steel so very little foam is generated. Spot mopping of milk stains may be required.

SAFETY & HANDLING PROCEDURE

Exposure to this material will cause permanent eye damage; splash-proof eye protection must be worn while handling **A-302**. This product will cause irritation and/or burning of skin. Prolonged or repeated contact may cause irreversible damage. Refer to MSDS for complete safety and handling techniques.

PHYSICAL PROPERTIES

Pounds per gallon.....	9.1-9.6
1% per pH	1.0-2.0
Appearance	Light Yellow
Odor	Pungent
Flash Point	NA

Seller Warranty

CH₂O brand test reagent refills are available through your sales representative at no charge. Customers are required to confirm product compatibility via a control test for their specific application. CH₂O recommends that you perform regular/daily testing to control chemical levels and cycles of concentration within established limits. Additional tests may be performed at your request. Test reports reflect conditions at the point when the analysis was performed. Results will change over time and with varying operating conditions.

Seller warrants that this product conforms to its chemical description and is reasonably fit for the purpose referred to in the directions for use when used in accordance with the directions under normal conditions. Buyer assumes the risk of any use contrary to such directions. Seller makes no other warranty or representation of any kind, express or implied, concerning the product, including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE. No such warranties shall be implied by law and no agent of seller is authorized to alter this warranty in any way except in writing with a specific reference to this warranty. The exclusive remedy against seller shall be a claim for damages not to exceed the purchase price of the product, without regard to whether such a claim is based upon breach of warranty or tort. Jurisdiction for any issues arising from or relating to this product shall be in the courts of the State of Washington and the venue shall be Thurston County. Any controversy or claim arising out of or relating to this contract, or breach thereof, shall be settled by arbitration in accordance with the rules and procedures as stated in RCW 7.06 and shall be binding upon both parties without right to appeal, and judgment upon the award rendered by the Arbitrator(s) may be entered in any court having jurisdiction thereof.

Applies to all products sold by CH₂O, Inc., and is hereby communicated to all of its customers as a condition of sale. Use of CH₂O products is subject to the Standard Terms and Conditions as listed on CH₂O, Inc.'s website at: www.ch2o.com.



VERSION DATE: November 11, 1997 REVISION DATE: September 2011

